

# FTXTP-N + RXTP-A



Indoor unit				FTXTP	25N	35N
Dimensions	Unit	HeightxWidthxDepth		mm	286 x770 x225	
Weight	Unit			kg	9	
Air filter	Type				Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m³/min	3.7 /5.0 /7.9 /11.0	
		Heating	Silent operation / Low / Medium / High	m³/min	4.4 / 5.5 / 9.0 / 10.5	
Sound power level	Cooling			dBA	58.0	
	Heating			dBA	58.0	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	21.0 /26.0 /43.0	
	Heating	Silent operation/Low/High		dBA	21.0 /26.0 /43.0	
Control systems	Infrared remote control				ARC480A53	
	Wired remote control				BRC073A1	

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit				RXTP	25A	35A
Dimensions	Unit	HeightxWidthxDepth		mm	605 x930 x376	
Weight	Unit			kg	42	
Sound power level	Cooling			dBA	60	
	Heating			dBA	60	
Sound pressure level	Cooling	Nom.		dBA	48.0	
	Heating	Nom.		dBA	49.0	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~46	
	Heating	Ambient	Min.~Max.	°CWB	-31 ~18	
Refrigerant	Type				R-32	
	GWP				675.0	
	Charge			kg/TCO2Eq	0.97 /0.66	
Piping connections	Liquid	OD		mm	6.35	
	Gas	OD		mm	9.50	
	Piping length	OU - IU	Max.	m	20	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference IU - OU			m	15.0	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	16	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTP + RXTP		25N + 25A		35N + 35A	
Cooling capacity	Min./Nom./Max.	kW		1.0 /2.5 /4.1		1.0 /3.5 /4.5	
Heating capacity	Min./Nom./Max.	kW		1.0 /3.2 /6.20		1.0 /4.0 /6.70	
Power input	Cooling	Nom.	kW	0.52		0.79	
	Heating	Nom.	kW	0.65		0.88	
Space cooling	Energy efficiency class			A+++			
	Capacity	Pdesign	kW	2.50		3.50	
	SEER			8.55		8.51	
	Annual energy consumption		kWh/a	102		144	
Space heating (Average climate)	Energy efficiency class			A++			
	Capacity	Pdesign	kW	2.50		3.00	
	SCOP/A			4.95		4.85	
	Annual energy consumption		kWh/a	707		866	
Space heating (Cold climate)	Energy efficiency class			A			
	Capacity	Pdesignh	kW	3.65		4.38	
	Annual energy consumption		kWh/a	1,937		2,426	
	SCOP/C			3.96		3.79	
Nominal efficiency	EER			4.88		4.45	
	COP			4.95		4.55	
	Annual energy consumption		kWh	260		395	
	Energy labeling Directive	Cooling/Heating		A/A			
Current - 50Hz	Maximum fuse amps (MFA)		A	16			

Daikin Europe N.V. Naamloze Venootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems, Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

ECPEN23-065 08/2023

